


Geberit PE torupõlv



Näitlik pilt



Kasutuseesmärk

- Hoonete veeärastuseks
- Krundi veeärastuseks

- UV-kindel

Tehnilised andmed

Materjal | PE-HD

Omadused

- Mõlemalt poolt elekterkeevismuhviga keevitav

| Tootenumber | DN | d, ø | arc | X | K |
|--------------|-----|--------|--------|--------|--------|
| 360.045.16.1 | 40 | 40 mm | 45 ° | 4 cm | 2 cm |
| 361.045.16.1 | 50 | 50 mm | 45 ° | 4.5 cm | 2 cm |
| 361.088.16.1 | 50 | 50 mm | 88.5 ° | 6 cm | 2 cm |
| 363.045.16.1 | 56 | 56 mm | 45 ° | 4.5 cm | 2 cm |
| 363.088.16.1 | 56 | 56 mm | 88.5 ° | 6.5 cm | 2 cm |
| 364.045.16.1 | 60 | 63 mm | 45 ° | 5 cm | 2 cm |
| 364.088.16.1 | 60 | 63 mm | 88.5 ° | 7 cm | 2 cm |
| 365.045.16.1 | 70 | 75 mm | 45 ° | 5 cm | 2 cm |
| 365.088.16.1 | 70 | 75 mm | 88.5 ° | 7.5 cm | 2 cm |
| 366.045.16.1 | 90 | 90 mm | 45 ° | 5.5 cm | 2 cm |
| 366.088.16.1 | 90 | 90 mm | 88.5 ° | 8 cm | 2 cm |
| 367.045.16.1 | 100 | 110 mm | 45 ° | 6 cm | 2.5 cm |
| 367.088.16.1 | 100 | 110 mm | 88.5 ° | 9.5 cm | 2.5 cm |
| 368.045.16.1 | 125 | 125 mm | 45 ° | 6.5 cm | 2.5 cm |
| 368.088.16.1 | 125 | 125 mm | 88.5 ° | 10 cm | 2.5 cm |
| 369.045.16.1 | 150 | 160 mm | 45 ° | 6.9 cm | 2 cm |
| 369.088.16.1 | 150 | 160 mm | 88.5 ° | 12 cm | 2.5 cm |
| 370.045.16.1 | 200 | 200 mm | 45 ° | 18 cm | 2.5 cm |